

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

5 **Listing of Claims:**

1. (Original) A method for monitoring the condition of a vehicle driver, in which a vehicle's position in a lane is detected and monitored, a direction of travel is determined, the actual position in the lane is compared
10 with the direction of travel which is determined, and the driver is assisted in maintaining the position in the lane,
characterized
in that a warning signal for the driver is generated when the
calculated direction of travel exactly matches the actual position in the lane
15 over a prespecified period of time.

2. (Original) The method as claimed in claim 1,
characterized
in that a visual and/or audible and/or haptic warning signal is
20 generated.

3. (Currently Amended) The method as claimed in ~~either of the preceding claims~~ claim 1,
characterized
25 in that a test signal, which depends on the driving situation, is added to the calculated direction of travel, and the warning signal is emitted when the vehicle follows the test signal.

4. (Currently Amended) The method as claimed in ~~one of the preceding claims~~ claim 1,
30 characterized

in that a deviation from the calculated direction of travel is determined, and the steering angle at which the steering wheel has to be steered to stay in the lane or to move into the lane is determined.

5 5. (Original) The method as claimed in claim 4,
characterized
in that a manual torque actuator (6) shifts the zero position of the steering torque by the determined steering angle.

10 6. (Currently Amended) The method as claimed in ~~one of the~~
~~preceding claims~~ claim 1,
characterized
in that driver assistance for staying in the lane increases
dynamically with the deviation from the calculated direction of travel.

15 7. (Currently Amended) The method as claimed in ~~one of the~~
~~preceding claims~~ claim 1,
characterized
in that driver assistance for staying in the lane is slowly
20 withdrawn when no lane is identified.

8. (Original) A condition-monitoring device (1) comprising a
lane-identification device (2), means (4) for determining a direction of
travel, a monitoring device (5) for monitoring deviations from the direction
25 of travel, and a warning device (11),
characterized

in that the warning device can be activated when the monitoring device detects that a specific direction of travel matches an actual direction of travel over a prespecified period of time.

5 9. (Original) The condition-monitoring device as claimed in claim
8,
characterized
in that a "steer-by-wire" system is provided.

10 10. (Currently Amended) The condition-monitoring device as
claimed in ~~either of claims 8 and~~ claim 9,
characterized
in that a manual torque actuator (6) is provided.

15 11. (New) The condition-monitoring device as claimed in claim 8,
characterized
in that a manual torque actuator (6) is provided.